

CLOSING WHEEL MOUNTING INSTRUCTIONS

Case IH 500 500T New Holland Drill with Eccentric Bolt

Before working on your planter or drill

DANGER: When storing or working on the drill always install cylinder stops or place the drill on stands to prevent personal injury or damage to the attachments.

PLEASE: Read instructions completely and verify all package contents before beginning installation.

1. Remove original closing wheel.
2. Slip the eccentric bolt over the drill arm, thread bolt into place, and loosely tighten set screws.
3. In this order, slide other kit parts over the bolt's threaded end:

EB ← 1/4" spacer ← cast wheel ← 1/2" spacer ← 5/8" nut

Be sure the wheel's angled spikes are pointed down in the back.

NOTE: These are the recommended starter settings.

Spacers can be placed as needed.

4. Adjust the eccentric bolt so that the cast wheel is angled in toward the row in the back and out/away in the front.
5. Tighten set screws and nut once wheel's pitch is set for proper closure of the seed furrow in the field.
6. Once you get one set to close the seed trench properly, you can use its set screw bolt setting as the gauge for setting all the rest of the rows.

Cast Closing Wheel Package Contents (per single row)

Item	Quantity
Closing Wheel (cast Mohawk or Zipper) . . .	1

IH500 Eccentric Bolt Package Contents (per single row)

Item	Quantity
Eccentric Bolt	1
<i>Eccentric Bolt includes 2 set screws</i>	
5/8" Nut	1
1/2" Spacer	1
1/4" Spacer	1
Instruction Sheet	1

