

REBOUNDER® MOUNTING INSTRUCTIONS

Case IH Precision Disk 500 Air Drill

Before working on your planter or drill

DANGER: When storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the attachments.

PLEASE: Read instructions completely and verify all package contents before beginning installation.

RUNNING FERTILIZER

#1: If applying liquids in furrow with the Rebounder, attach either Y-Not Split It, Hose Holder, or Straight Shot kit by following kit directions.

INSTALL KIT BEFORE INSTALLING REBOUNDER TO PLANTER UNIT. SEE KIT INSTRUCTIONS.

Rebounder Package Contents (per single row)

Item	Quantity
4-Hole Rebounder	1
Instruction Sheet	1

Bracket Package Contents (per single row)

Item	Quantity
Mounting Bracket (Left or Right)	1
1/4" x 3/4" Whiz Bolt	2
1/4" Whiz Nut	2

MOUNTING REBOUNDER TO BRACKET

#2: Place the Rebounder behind the left or right mounting bracket.

Rebounder: Place bolts in 3rd & 4th holes from the top

Mounting Bracket: Place bolts in 2nd & 4th holes from the top

Do not tighten bolts yet.



MOUNTING REBOUNDER & BRACKET TO SEED BOOT



#3: Remove these bolts from the top of the seed boot.

Place mounting bracket under existing bolts, leaving the scraper shim under the bracket.

Replace and tighten bolts over the mounting bracket.

Center Rebounder and tighten whiz bolts.



Rebounder covered by one or more of the following U.S. patents: 5,640,915; 5,918,557; 6,082,275; 6,283,050; 6,453,832; 6,763,773 and 7,121,216.