

REBOUNDER® MOUNTING INSTRUCTIONS

K Hart Air Drills

Before working on your planter or drill

DANGER: When storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the attachments.

PLEASE: Read instructions completely and verify all package contents before beginning installation.

Before



If applying liquids in furrow with the Rebounder, attach either Y-Not Split It, Hose Holder, or Straight Shot kit. See kit instructions.

**INSTALL KIT BEFORE
INSTALLING REBOUNDER TO
PLANTER UNIT.**

Rebounder Package Contents (per single row)	
Item	Quantity
3-Hole Rebounder	1
Instruction Sheet	1
Bracket Package Contents (per single row)	
Item	Quantity
Salford Mounting Bracket	1
1/4" x 1" Bolt	2
1/4" Whiz Nut	2
3/8" x 1-1/4" Bolt	2
3/8" Lockwasher	2
3/8" Whiz Nut	2

Place the Rebounder on the top of the bracket.

BOLTS GO THROUGH:

Top and center hole on the Rebounder


1st and 3rd holes from the top on the mounting bracket



After



The Rebounder should be at an approximately 30° angle



double discs need to be where spoon starts widening out

Mount the Rebounder and mounting bracket to the front side of the slotted hole in the present flapper bracket.

Normally the Rebounder is run at a 30 degree angle to the soil surface. The spoon of the Rebounder needs to be down into the seed V and the tip end of the Rebounder needs to run about 3/8" off the bottom.

The holes in the Rebounder are spaced at 3/4" apart and the 4 holes in the bracket are spaced 3/8" apart so you can move the Rebounder up and down in 3/8" increments.

HELPFUL HINTS FOR MOUNTING THE REBOUNDER™ ON DRILLS

(Read Instructions Completely before Beginning Installation)

Before working on your planter or drill

DANGER: When storing or working on the drill always install cylinder stops or place the drill on stands to prevent personal injury or damage to the Rebounder.

WARNING: Do not roll back or back up the drill in or on the ground as this can result in damage to the Rebounder.

Helpful Hints

Step #1: use a farm jack on the press wheel to raise up the drill unit 3-4" before you mount the first row.

IMPORTANT: have press wheel adjusting handle of knob, in the position you would normally run in the field (see **fig (a)**).

Step #2: slide a board or piece of flat iron under the double disc openers and back under the press wheel tire. The board or flat iron represents the bottom of the seed V.

Step #3: now you can bolt the Rebounder to the bracket on the drill. Using the 1/4" bolts attach the Rebounder to the bracket on the drill.

Step #4: variances in the disc blade size will occur among individual drills as well as within any single drill. Measure discs behind the tire track rows. If they are worn more than other rows this process may need to be used to set these rows also.

Step #5: if replacing Rebounders on previously installed brackets, simply remove the old Rebounder without removing the disc blade. Using a small bar magnet or a long handled magnet, place the bolt on the magnet and slide it up between the discs and into the holes of the bracket and the Rebounder. This allows you to come in behind with a wrench or socket to install and tighten the nuts.

