

SALFORD DRILL REBOUNDER MOUNTING INSTRUCTIONS

(Read Instructions Completely before Beginning Installation)

Before working on your planter or drill

DANGER: when storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the Rebounder. **WARNING:** do not roll back or back up the planter in or on the ground as this can result in damage to the Rebounder.

Mounting Instructions

Before you begin, verify all items listed in the "package contents" table at the right.

- Step #1:** if using the optional fitting kit for liquid placement in furrow, install the kit on the Rebounder at this point, if not continue to step #2.
- Step #2:** remove 1 closing disc to expose the center mounting bracket as shown (fig. (a))
- Step #3:** Mount the Rebounder (using holes #3 and #4) to the mounting bracket as shown (fig. (b)). Make sure that the L bracket (if using an optional fitting) is installed as shown in the diagram below. Tighten all nuts and bolts on the Rebounder.
- Step #4:** Install the 2 provided 3/8 x 1/2 bolts to secure the bracket to the drill, center row unit as shown (fig. (c)).
- Step #5:** Install the black hose clamp (fig. (d)), with the hose running through the L bracket on the Rebounder first and then place the tube through the black clamp. Thereafter remove the nut and secure the black clamp by tightening the nut.

NOTE: 1/4 hose, L bracket and black 1/4 hose holder are part of the optional fitting kit.


Rebounder (DOSALFORD) Package Contents (per single row)

Item	Quantity
Rebounder (drill type)	1
1/4 x 7/8" bolt	2
1/4" whiz nut.	2
1/4" tube clamp	1
3/8" nut	1
L-bracket	1
Instruction Sheet	1

Bracket (DOSALFORDBKT) Package Contents (per single row)

Item	Quantity
Bracket	1
3/8 x 1/2" bolt	2

Optional fittings are available for fertilizer/chemical applications. Options include, Y-Not Split-It, Straight Shot, or Hose Holder kits, each available for an additional charge.



HELPFUL HINTS FOR MOUNTING THE REBOUNDER™ ON DRILLS

(Read Instructions Completely before Beginning Installation)

Before working on your planter or drill

DANGER: When storing or working on the drill always install cylinder stops or place the drill on stands to prevent personal injury or damage to the Rebounder.

WARNING: Do not roll back or back up the drill in or on the ground as this can result in damage to the Rebounder.

Helpful Hints

Step #1: use a farm jack on the press wheel to raise up the drill unit 3-4" before you mount the first row.

IMPORTANT: have press wheel adjusting handle of knob, in the position you would normally run in the field (see **fig (a)**).

Step #2: slide a board or piece of flat iron under the double disc openers and back under the press wheel tire. The board or flat iron represents the bottom of the seed V.

Step #3: now you can bolt the Rebounder to the bracket on the drill. Using the 1/4" bolts attach the Rebounder to the bracket on the drill.

Step #4: variances in the disc blade size will occur among individual drills as well as within any single drill. Measure discs behind the tire track rows. If they are worn more than other rows this process may need to be used to set these rows also.

Step #5: if replacing Rebounders on previously installed brackets, simply remove the old Rebounder without removing the disc blade. Using a small bar magnet or a long handled magnet, place the bolt on the magnet and slide it up between the discs and into the holes of the bracket and the Rebounder. This allows you to come in behind with a wrench or socket to install and tighten the nuts.

