

REBOUNDER® MOUNTING INSTRUCTIONS

Replacement for Wraparound / Universal Seed Firmers

Before working on your planter or drill

DANGER: When storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the attachments.

PLEASE: Read instructions completely and verify all package contents before beginning installation

NOTE: Rebounder and bracket designed to replace the consumable parts of the Wraparound and Universal seed firmer assembly, allowing for repair of worn-out or poorly functioning seed firmer assemblies

Step #1:

If applying liquids in furrow with the Rebounder, attach either Y-Not Split It, Hose Holder, or Straight Shot kit by following kit directions.

INSTALL KIT BEFORE INSTALLING REBOUNDER TO PLANTER UNIT. See kit instructions.

Step #2:

Use the two t-nuts, washers, and t-nut screws to bolt the Rebounder on top of the mounting bracket.

The t-nuts and washers will go through the 2nd and 4th (bottom) holes of the mounting bracket and the middle and bottom of the Rebounder.

Secure t-nuts with the two t-nut screws on the under side of the mounting bracket.



NOTE: The unused holes are not for adjusting the Rebounder up and down. Once the Rebounder is mounted, you are set to go—no adjustments needed.

Step #3:

Loosen the bolt holding the Seed Firmer in the seed boot.

Remove the old firmer, and replace it with the new Rebounder and mounting bracket.

Loosely re-tighten the bolt (just enough so there is pressure against the Rebounder).



Rebounder Package Contents (per single row)	
Item	Quantity
Rebounder (3 hole)	1
T Nut	2
T Nut Screw	2
Washer	2
Instruction Sheet	1

Bracket Package Contents (per single row)	
Item	Quantity
Mounting Bracket.	1

NOTE:

This mounting bracket is no longer black; it is now green.

