

G2 UPDATE KIT

John Deere 7000 / 7100 / 7200 / 7300

Before working on your planter or drill

DANGER: When storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the attachments.

PLEASE: Read instructions completely and verify all package contents before beginning installation

JD 7000 / 7100		
PART PHOTO	PART #	QUANT.
	P86763(1)	1
	P64237	1
	P55143	1
	P2204B	2
	P74643	1
	P48430	2
-	-	-
	02060270 (5/8" x 3-1/2" wheel bolt)	2
	14030073 (5/8" lock nut)	2
	M12 x 1.75 . 50 bolt	2
	M12 lock nut	2
	1/2" ZIPPER SPACERS (5/8" x 7/8" x 1/2" bushing)	2
	1/4" ZIPPER SPACERS (5/8" x 7/8" x 1/4" bushing)	2
Press wheels with 5/8" bore bearing (sold separately)		2

JD 7200 / 7300		
PART PHOTO	PART #	QUANT.
	P86763(2)	1
-	-	-
	P55143	1
-	-	-
-	-	-
	P48430	1
	P55888	1
	02060270 (5/8" x 3-1/2" wheel bolt)	2
	14030073 (5/8" lock nut)	2
	M12 x 1.75 . 50 bolt	2
	M12 lock nut	2
	1/2" ZIPPER SPACERS (5/8" x 7/8" x 1/2" bushing)	2
	1/4" ZIPPER SPACERS (5/8" x 7/8" x 1/4" bushing)	2
-	-	-

OVER →

G2 UPDATE KIT

John Deere 7000 / 7100 / 7200 / 7300

Before working on your planter or drill

DANGER: When storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the attachments.

PLEASE: Read instructions completely and verify all package contents before beginning installation

7200 / 7300



Before installing the JD 7200 & 7300 series tail upgrade, you need to use a die grinder on the sheet steel sides of your row unit so that the ears on the eccentric will go into the unit.

7000 / 7100

