

# HOSE HOLDER MOUNTING INSTRUCTIONS

## for Planters with John Deere type Rebounder

**Before working on your planter or drill**

**DANGER:** When storing or working on the planter always install cylinder stops or place the planter on stands to prevent personal injury or damage to the attachments.

**WARNING:** Do not roll back or back up the planter in or on the ground as this can result in damage to the Rebounder.

**PLEASE:** Read instructions completely and verify all package contents before beginning installation.

### ! IMPORTANT POINTS !

- The holder in this kit acts as a guide keeping the disc from rubbing on the 1/4" fertilizer or chemical hose.
- The Hose Holder must be mounted to the Rebounder before the Rebounder is attached to the seed tube.
- **DO NOT STRAP ANY LARGE TIE AROUND ANY PART OF THE HOSE.** The hose must be able to flex independently with the Rebounder.

### Hose Holder for JD type

PART # **HH** Package Contents (per single row)

Item	Quantity
3/8" Clear Hose . . . . .	1
1/4" Orange Hose . . . . .	1
Metal Plate . . . . .	1
12 x 3/8" Phillips Screws . . . . .	2
Propeller T-Nut . . . . .	1
#10-24 x 1/2" Screw for T-Nut Slotted . . . . .	1
Washer . . . . .	1
L Bracket . . . . .	1
Instruction Sheet . . . . .	1

1. Take the propeller t-nut (fig. (a)) and insert it into the hole on the backside of the Rebounder saw tooth insert (fig. (b)) using a hammer or pliers to press it into the plastic.
2. Turn the saw tooth insert over, placing it into the Rebounder (see Rebounder mounting instructions for proper placement of the saw tooth).  
Now place the L-bracket (fig. (c)) with the small hole on the Rebounder with the washer (fig. (d)) on top, over the hole of the propeller t-nut.
3. Using a screw driver, tighten the round-head, slotted (#10-24 x 1/2") screw (fig. (e)) into the propeller t-nut.
4. Slice through one side of the short piece of clear plastic hose (lengthwise), then place it over the 1/4" orange hose about 2" from end of 1/4" hose (fig. (f)).
5. In order to run the fertilizer or chemical hose to the end of the Rebounder, you must first run the hose through the large hole on the L-bracket (fig. (g)).
6. Then run the tube through the raised area that holds the screws and the hole in the molded-in tab at the end of the Rebounder.  
**Extend the hose past the end of the Rebounder tip approximately 3/8".**
7. Place the screws in the metal plate, over the clear hose that is over the orange hose and screw the metal plate down to the Rebounder to hold the hose in place (fig. (h)).
8. Attach Rebounder to the seed tube (see Rebounder Mounting Instructions for your planter type).

